




RINFORZATA CRESTATA CP / RIDGED CP REINFORCED

POLIURETANO / POLYURETHANE	AZZURRA - BLUE		Durezza - Hardness		80Sh	
			Temperatura ideale Saldatura / Advised Welding Temperature		240°C	
			Temperatura Esercizio / Temperature Range		-30°C/+60°C	
			Coefficiente d'attrito / Friction Coefficient		Acciaio / Steel - 0,51	
			Pretensionamento=Sviluppo / Tensioning=Length		-1,5%	
	Sezione Section	Dimensioni Sizes	Carico max / Max Load Kg.	Diam. Pulegge / Pulley Diam. mm	Peso / Weight Kg/mt	Lung. Rotolo / Roll length mt
	A	13x15	17	110	0,16	30
	B	17x20	28	130	0,26	30
	C	22x25	47	190	0,44	30
POLIURETANO / POLYURETHANE	BIANCO - WHITE		Durezza - Hardness		85Sh	
			Temperatura ideale Saldatura / Advised Welding Temperature		240°C	
			Temperatura Esercizio / Temperature Range		-30°C/+75°C	
			Coefficiente d'attrito / Friction Coefficient		Acciaio / Steel - 0,51	
			Pretensionamento=Sviluppo / Tensioning=Length		-1,5%	
	Sezione Section	Dimensioni Sizes	Carico max / Max Load Kg.	Diam. Pulegge / Pulley Diam. mm	Peso / Weight Kg/mt	Lung. Rotolo / Roll length mt
	A	13x15	31	160	0,16	30
	B	17x20	44	180	0,26	30
	C	22x25	72	210	0,44	30
POLIURETANO / POLYURETHANE	VERDE - GREEN		Durezza - Hardness		85Sh	
			Temperatura ideale Saldatura / Advised Welding Temperature		240°C	
			Temperatura Esercizio / Temperature Range		-30°C/+75°C	
			Coefficiente d'attrito / Friction Coefficient		Acciaio / Steel - 0,51	
			Pretensionamento=Sviluppo / Tensioning=Length		-1,5%	
	Sezione Section	Dimensioni Sizes	Carico max / Max Load Kg.	Diam. Pulegge / Pulley Diam. mm	Peso / Weight Kg/mt	Lung. Rotolo / Roll length mt
	A	13x15	31	160	0,16	30
	B	17x20	44	180	0,26	30
	C	22x25	72	210	0,44	30
POLIURETANO / POLYURETHANE	TRASPARENTE - TRANSPARENT		Durezza - Hardness		85Sh	
			Temperatura ideale Saldatura / Advised Welding Temperature		240°C	
			Temperatura Esercizio / Temperature Range		-30°C/+75°C	
			Coefficiente d'attrito / Friction Coefficient		Acciaio / Steel - 0,51	
			Pretensionamento=Sviluppo / Tensioning=Length		-1,5%	
	Sezione Section	Dimensioni Sizes	Carico max / Max Load Kg.	Diam. Pulegge / Pulley Diam. mm	Peso / Weight Kg/mt	Lung. Rotolo / Roll length mt
	A	13x15	31	160	0,16	30
	B	17x20	44	180	0,26	30
	C	22x25	72	210	0,44	30