


VERDE - GREEN




Sezione
Section

Dimensioni
Sizes

A	13x8
B	17x11
C	22x14

Durezza - Hardness		85Sh	
Temperatura ideale Saldatura / Advised Welding Temperature		240°C	
Temperatura Esercizio / Temperature Range		-30°C/+75°C	
Coefficiente d'attrito / Friction Coefficient		Acciaio / Steel - 0,51	
Pretensionamento=Sviluppo / Tensioning=Length		-1,5%	
Carico max / Max Load Kg.	Diam. Pulegge / Pulley Diam. mm	Peso / Weight Kg/mt	Lung. Rotolo / Roll length mt
21	50	010	30
35	90	0,18	30
58	110	0,29	30

TRASPARENTE - TRANSPARENT



Sezione
Section

Dimensioni
Sizes

A	13x8
B	17x11
C	22x14

Durezza - Hardness		85Sh	
Temperatura ideale Saldatura / Advised Welding Temperature		240°C	
Temperatura Esercizio / Temperature Range		-30°C/+75°C	
Coefficiente d'attrito / Friction Coefficient		Acciaio / Steel - 0,51	
Pretensionamento=Sviluppo / Tensioning=Length		-1,5%	
Carico max / Max Load Kg.	Diam. Pulegge / Pulley Diam. mm	Peso / Weight Kg/mt	Lung. Rotolo / Roll length mt
21	50	010	30
35	90	0,18	30
58	110	0,29	30